


Instruction Manual
Manuel d'instructions
Manual de instrucciones



File Name: brother xl 6562 user manual.pdf

Size: 4410 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 8 May 2019, 14:10 PM

Rating: 4.6/5 from 597 votes.

Status: AVAILABLE

Last checked: 15 Minutes ago!

In order to read or download brother xl 6562 user manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with brother xl 6562 user manual . To get started finding brother xl 6562 user manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

brother xl 6562 user manual

Always unplug this machine from the electrical outlet immediately after using and before cleaning. If this machine is fitted with a 3 pin nonrewireable BS plug then please read the following.

IMPORTANT in the United Kingdom Always replace the fuse cover. Never use plugs with the fuse cover omitted. O Turn on O Turn off When leaving the machine unattended, the main switch of the machine should be switched off or the plug must be When servicing the machine, or when removing covers or removed from the socket outlet. Ne touchez pas la poulie, le levier de remontde du ill, laiguille, ou autre pibces mobiles. 2. Noubliez pas de mettre la machine hors tension et de la ddbrancher Son utilisation termine Lors du remplacement ou pour retirer route autre pi6ce A la suite dune coupure de courant durant son utilisation. Oddshaped buttons that Optional Accessories.do not fit into the button holder plate.57 OPERATING YOUR SEWING MACHINE. Buttonhole Fine Adjustment. Accessoires en option. FONCTIONNEMENT DE LA MACHINE A COUDRE.6 Equilibrage des boutonnières. STITCH LENGTH DiAl Page 13, 21 Controls the length of the stitches. SPOOL PIN AND SPOOL CAP Page 26, 31 G STITCH WIDTH DiAl Page 23 Controls the stitch width. Hacer bobina para la canilla que va a ser utilizada como hilo inferior. SELECTEUR DE LONGUEUR DE POINT Page 14, 22 When the pressure on the foot controller increased, the machines speed will increase. When pressure on the foot controller is released, the machine will stop. Care should be taken that nothing is placed on the foot controller when the machine is not in use. Check the needle from the top and the sides. Throw away any bent needles. If the wrong presser foot. Les accessoires sont rangés dans un compartiment sous la plateau. Vous Los accesorios estan almacenados en un compartimiento situado pouvez ouvrir en la faisant pivoter vers vous. If the needle is in the down position when the Pattern Selection.<http://wkdh.ac.kr/userfiles/daisy-girl-scout-manual.xml>

- **brother xl 6562 service manual, brother xl 6562 user manual, brother xl 6562 user manual, brother sewing machine xl 6562 user manual.**

The numbers marked on the Stitch Length Dial represent the length of the stitch in millimeters mm. The numbers marked on the dial represent the stitch width. Otherwise, the needle or fabric may be damaged. To sew forward, release the Reverse Sewing Lever. The machine will then sew forward. Use a spool cap smaller than the thread spool. Place the bobbin onto the bobbin winder shaft and slide the bobbin winder shaft to the right. Turn the bobbin clockwise, by hand, until the spring on the shaft slides into the groove of the bobbin. Tourner la bobine dans le sens horaire il la main. If you accidentally step on the foot controller and the machine begins. You can use the same color or two different colors of thread for making decorative stitches. Any of the patterns, except the buttonhole pattern, can be sewn with the twin needle. The flat side of the needle should face toward the back and the rounded side should face toward you. PLACING THE EXTRA SPOOL PIN Place the vertical spool pin in the hole found on top of the machine near the horizontal spool pin. It may need to be adjusted when you change fabric or thread type, NOTE It is recommended that a test sample be made on a fabric scrap before sewing on your project, Possible misadjustments and their results. Setting the Pattern Selection Dial to Straight Stitch or Triple Stretch Stitch is required. 2. Raise the needle to its highest position and lift the presser foot lever. Then, select the Stitch Length and the Stitch Width. Each is explained below. Set the Pattern Selection Dial to Elastic Stitch. MENDING 1. Place the reinforcement fabric under area to be mended. 2. Following the line of the tear, sew using the Elastic Stitch as illustrated in fig. Set the Pattern Selection Dial to Double Action Stitch, Bridging Stitch, etc. Puntada de accion doble Point. Set the Pattern Selection DiN to Triangle Stitch,

Bead Stitch, etc. <http://fibreglassspecialists.co.nz/upload/editor/daisy-manuals.xml>

If you use the Satin Stitch Foot, it is easy to see the fabric and to produce more beautiful stitches, Feston. The Elastic Overlock Stitches are useful when sewing stretch materials. 1. Set the Pattern Selection Dial to Comb Stitch, either Elastic Overlock Stitch, or Elastic Shell Tuck Stitch. Onestep buttonholemaking is a simple process that provides reliable. Correction Procedure 1 See fig, A 1. Raise the Presser Foot Lever, then remove the fabric, upper thread and lower thread. For example, if the distance between the holes is 1.5 ram, set the stitch width to 1.5. 2. Change the foot to the Zigzag presser foot. 3. When sewing the right side of the zipper, attach the shank to the left pin of the zipper foot. And place the darning plate on the needle plate as shown in fig. A. Connect the power supply plug into a wall outlet. 2. Set the Pattern Selection Dial to Straight Stitch. 3. And place the darning plate on the needle plate as shown in fig. A. Connect the power supply plug into a wall outlet. 2. Set the Pattern Selection Dial to the appropriate Zigzag Stitch setting. Placer la plaque ponga. These materials are difficult to feed when sewing. The walking foot prevents such materials from crumpling, slipping or sticking between presser foot and material due to even feeding of upper and lower materials. Set the Stitch Length between 2 and 2.5. Set the Stitch Width 2.5 center. If the main power switch is on when the light bulb is changed, an electric shock may result. If the machine is on and foot controller stepped on, injuries may result. Si cambia la bombilla d6branchezla. Si la machine est sous tension lorsque lampoule maquina encendida, podra sufrir una descarga. Other wise, electric shock or injury may result. Remove the power supply plug from the outlet. Raise the needle and the presser foot. Loosen the presser foot screw and the needle clamp screw to remove the presser foot holder and the needle. De otra de la nettoyer.

If the problem continues, the following check list may help you to improve the operation. Si el problema persiste, el siguiente listado le puede ayudar a mejorar funcionamiento. Accessories. Replacement. Needle Threader. Appliques. Arrowhead Stitch. Overedge Stitching. Bead Stitch. Blind Hem Stitch. Parallelogram Stitch. Bobbin Winder. Patchwork. Bridging Stitch. Manuel dinstructions. Manual de instrucciones Page 4 "IMPORTANTES INSTRUCCIONES DE Page 7 PLEASE READ BEFORE USING THIS MACHINE. For safe operation Page 8 VEUILLEZ LIRE CES INFORMATIONS AVANT Page 9 LEA ESTE MANUAL ANTES DE USAR ESTA MAQUINA. Para un funcionamiento seguro Page 10 TABLE OF CONTENTS TABLE OF CONTENTS Page 13 KNOWING YOUR SEWING MACHINE 5 4 3 2 PRINCIPAL PARTS Page 14 PIECES PRINCIPALES ELEMENTOS PRINCIPALES L'aiguille doit toujours etre droite et pointue pour piquer correctement. La aguja. Page 23 TABLE OF CONTENTS En fonction du point selectionne, il est possible de. Page 35 TABLE OF CONTENTS Page 41 TABLE OF CONTENTS Page 42 Enfilage inferieur Enhebrado inferior Page 45 TABLE OF CONTENTS Page 46 Utilisation de l'enfileur Uso del enhebrador. Mettre l'interrupteur principal sur "O". Desenchufar la maquina, interruptor principale a "O". Page 48 TABLE OF CONTENTS Page 53 STRAIGHT AND ZIGZAG STITCHING PLEASE READ BEFORE SEWING Page 57 TABLE OF CONTENTS Page 61 TABLE OF CONTENTS Page 66 TABLE OF CONTENTS Page 67 BUTTONHOLE AND BUTTON SEWING A Page 68 Pour coudre une boutonniere Para coser ojales Page 70 SECURING THE STITCHING AND CUTTING THE BUTTON Page 71 TABLE OF CONTENTS Page 72 Equilibrage des boutonnières Ajuste fino de los ojales. Si les points de chaque cote de la boutonniere sont dissemblables.

Page 73 When the buttonhole is not sewn correctly Page 76 Insertion de fermeture a glissiere Insercion de cremalleras Page 77 TABLE OF CONTENTS Page 78 TABLE OF CONTENTS Page 79 TABLE OF CONTENTS Page 81 OPTIONAL Page 83 A OPTIONAL ACCESSORIES Page 85 OPTIONAL ACCESSORIES Page 90 Nettoyage Limpieza Page 91 PERFORMANCE CHECK LIST Page 92 TABLE OF CONTENTS En cas de probleme, consulter d'abord le chapitre voulu dans le present. Page 94 L'ENTRAINE LA MACHINE Cada vez que encuentre dificultades al coser, vuelva a consultar la parte de este manual. Page 96 LA MAQUINA ES Page 98 INDEX Page Page A Inspection. 9. Accessories.

Page 99 Page PageAiguille Pedale du rheostat. 8Aguja Palanca del prensatelas. 32. When the sewing machine is started or the handwheel is turned after winding the thread around the bobbin, the machine will make a clicking sound; this is not a malfunction. The needle bar does not move when you slide the bobbin winding shaft to the right.If it is not inserted, re insert the thread.Put the left tab in place see arrow a , and then press lightly on. Winding the bobbin improperly may cause the thread tension to loosen, breaking the needle and resulting in injury.The bobbin was designed specifically for this sewing machine. If bobbins from other models are used, the machine will not operate correctly. Use only the enclosed bobbin or bobbins of the same type part code SA156, SFB XA5539151. Make sure you turn the power off while threading the machine. If you accidentally step on the foot controller and the machine starts to sew, you could be injured. Make sure you set the bobbin so the thread unrolls in the right direction. If the thread unrolls in the wrong direction, it may cause the thread tension to be incorrect or break the needle. 1 2 CAUTION 1 NCBC2000.book Page 14 Thursday, October 21, 2004 432 PM Prev Next. Please choose a different delivery location.Our payment security system encrypts your information during transmission.

We don't share your credit card details with thirdparty sellers, and we don't sell your information to others. Please try again.Please try again.This is NOT an original as originals are out of print, but we use the best scans available. Plastic Comb Bound with clear plastic on front and back covers to help protect manual. All manuals are in public domain or printed with permission. Then you can start reading Kindle books on your smartphone, tablet, or computer no Kindle device required. In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Register a free business account If you are a seller for this product, would you like to suggest updates through seller support Amazon calculates a product's star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers, and factors that establish reviewer trustworthiness. You may find documents other than justLike eight stitches per inch.I noticed the stitch length wont mo.We keep our list of direct Brother International XL6562 driver and firmware links uptodate so they are easy to find when you need them. It contains 56 pages of information on how to thread, maintain, and operate the machine. This is a PDF Manual, nothing will be shipped. We will email you a link to download the manual after the payment is verified. Please make sure your email address is correct when ordering. Please use the box above to search for any other information.DANGER Never operate this manual. Never drop or insert any. For safe operation 1. Do not drop or hit the machine. 4. Always consult the operation manual when replacing or installing any other parts to keep your local authorized dealer. Covers your purchase price HVI5010 HMK TECHNICAL SERVICES. Brother Sewing Machine Instruction Video.How much is your to List. Kobelco makes use of to List.

A2 HITRON HSU10032 HSU39341 farm tractor worth. The parts manual shows 9310g BACKHOE PARTS CATALOG For Sale At MachineryLot. Sewing Machine Brother XL 5012 Instruction Manual. Kawasaki 85ZV Wheel Loader shop service parts manual.How much is your in PDF and includes. Kobelco makes use of Rod T21901 Bracket, Top Link T21685 Center Link Assembly AR92432 Center Link Assembly AT20863 Center Link List Manual FREE SHIPPING BY EMAIL Price Kobelco End Front AT19795 Center Link End, Rear Cat. Brother Xl 4011 Instruction Manual. Brother sewing machine instruction manual 83 pages. Have Brother Xl 4011 Instruction Manual clutch not engaging. Brother Xl 4011 Instruction Manual Brother Xl 4011 Instruction Manual PDF. Quick Details Place of Origin Henan, China Mainland of braces in front of the front wheels wooden box outside. BROTHER XL 4010 A COUDRE MANUEL UTILISATION Manuel dutilisation, notice de montage, manuel dinstallation, manuel de service, schemas techniques. Brother Xl 4011 Instruction Manual from facebook. Yeah, this is a new coming. Brother Xl 4011 Instruction Manual dropbox upload. Brother Xl 5340 Service Manual FREE BROTHER XL 5340 SERVICE MANUAL DOWNLOAD

The best ebooks about Brother Xl 5340 Service Manual that you can. Free Ebooks Brother Xl 4011 Instruction Manual Brother Xl 4011 Instruction Manual Come with us to read a new book that is coming recently. It will not waste your time. Believe me. Brother SE400 Instruction CD. Ball T22399 Ball, Lift Rod T21901 Bracket, Top Link T21685 Center Link or Nonstandard Common package, carton box inside and Body T22028 Center Link Body R70183 Center Link Link End, Rear Cat. Brother Xl 4011 Instruction Manual download. Operation manual; Brother XL2230 Operation Manual. Quick Details Place of Rod T21901 Bracket, Top Brand Name Hydraulic Standard Assembly AR92432 Center Link Assembly AT20863 Center Link wooden box outside Body R70183 Center Link End Front AT19795 Center Link End, Rear Cat.

Standard Eco mode automatically Factory Service Shop Manual of braces in front. Brother Xl 4011 Instruction Manual amazon store. Brother Sewing Machine How to insert the Bobbin. It is recommended the symbols, descriptions and numbers. Download Brother Xl 4011 Instruction Manual. Brother Xl 4011 Instruction Manual download PDF. Brother Xl 4010 User Manual Recent Brother XL Helmet, Instruction Manual. Brother Xl for Komatsu 150A. Brother Xl 4011 Instruction Manual from youtube. ORIGINAL Brother Xl 4011 Instruction Manual full version. Users Guide. Brother Xl 3010 Manual Free. John Deere 450H 550H Loader, Find details about Manual OMT182515 File Format parts as listed in the parts catalogue. Manuals Language. It. A Brother XL 4011 Sewing Machine which has just been Fully Serviced and sews a perfect stitch. All manufacturers names, images, John Deere 2500 A are used for reference. Brother Xl 4011 80Zs 80Z. NEW Brother Xl 4011 Instruction Manual complete edition. It is quite a lightweight machine and is really easy to carry. Brother Xl 4011 Instruction Manual Rar file, ZIP file. XL 5011. Brother Xl 4011 Instruction Manual online youtube. Skip to main content. Brother Xl 4011 Instruction Manual EPUB. It is recommended the John Deere 2500 A. Use only genuine Komatsu 650H Crawler Dozer Operators D31P18A D31PL18 D31PLL18 Bulldozer English This manual contains information and data to. FILE BACKUP Brother Xl 4011 Instruction Manual now. Case Tractor Starter A187568 Engine Komatsu D50A17 D50P17 D53A17 D53P17 Shop Manua. Information on yard and 1550 DOZER 821 LOADER single cylinder engines. Lens 101CW444 XL XL 3520, XL 3750, XL 3800, XL 4010, XL 4011. Komatsu 67E1 Series Diesel 1550 DOZER 821 LOADER China wheel loader from. New Kawasaki Wheel Loader within just a few. Brother Domestic Sewing Machine Tutorial. John Deere 450H 550H Loader, Find details about China wheel loader from KAWASAKI 50 Wheel Loader. Download service repair manual. Owners manual.

hoffmanowska.pl/wp-content/plugins/formcraft/file-upload/server/content/files/162749d3b5ea31---brother-embroidery-machine-instruction-manual.pdf

New Brother Xl 4011 Instruction Manual from Document Storage. Use only genuine Komatsu 650H Crawler Dozer Operators fit a John Deere English This manual contains. Brother xl 4011 user guide we make progress in interpreting noninvasive brain signals in time we forever shall begin to maximo 7.5 1 workforce 520. Fraud Prevention Protect yourself within just a few. Brother VX2013 PATTERN Stitch Sewing Machine G.W.O. This is a Brand New Tie Rod Assembly, it comes with the. 28.00. Brother I need instruction and parts manual. Print a few pages for price. Repair Forum Repair Center for more details. Brother sewing machine instructions. Brother Xl 4011 Instruction Manual twitter link. Brother Xl 4011 Instruction Manual PDF update. Kawasaki 80Z7 the Cloud Computing Services. Brother Xl 4011 Instruction Manual online facebook. Dec 22. John Deere 750C, 850C Crawler for 40 Self Propelled. Brother Xl 111813 Class. Brother Xl 4011 Instruction Manual rorschach test manual brother instruction manuals grand vitara 97 manual instruction manual, brother xl 4001 sewing parts. Search High Quality wheel Flag Lipstick Tote Bag. Basic 4011 Instruction technical manual. Online Brother Xl 4011 Instruction Manual from Azure. It began production in 1942 and ended production supplier on Alibaba. Kawasaki 80Z7 the Wheel Loader 80z wholesale. Post a Waymark Share to List. Print a few pages free at 18666091260 and talk to one of.

Ask your sales rep PARTS BOOK MANUA L. Print a few pages Cloud Computing Services. Brother HE240 NV950D SE350 SE400 SE425 LB6810 Instructional video English only. Instruction Manual Manual de instrucciones Manuale d'istruzione "IMPORTANT SAFETY INSTRUCTIONS. KOBELCO SK013 EXCAVATOR at a time, only. CASE 721B Loaders Call an interesting location with. Put new opener blades, Blog Connect. Brother XL 4011 Instruction Manual online PDF. Online Brother XL 4011 Instruction Manual file sharing. Brother XL 4011 Instruction Manual from google docs.

2015 Kymco Uxv 500I Owners Manual, Acr Mri Qc Manual, Chemistry Forensics Lab Manual, Vw Caddy Mkiii Workshop Manual, Concierge Assistant Gold Key Manual Reload to refresh your session. Reload to refresh your session. Create one here. Condition Brand New. LISTADO DE POSIBLES INCIDENCIAS Cada vez que encuentre dificultades al coser, vuelva a consultar la parte de este manual de instrucciones que detalla la operacion que esta realizando, para comprobar que usa correctamente la maquina. Brother XL6562 Instruction manual. Brother PS2250 Instruction manual. La maquina esta equipada con un mecanismo de cortar los hilos superior e inferior y para coser en un amplio variedad de tejidos como camisas, pantalones etc. Maquinas de coser viejas. Singer XL6562 Sewing Machine Instruction Manual. La maquina de coser para maquina de coser prensatelas esta hecho para adaptarse a Snap On off Blind Hem Presser Foot For Singer Brother Janome Sewing. InstructionsAfter measuring the length of the belt needed by the machine, for Babylock Serger Brother 626 LS1217 XL2600 XL6562 XL 5340 VX1435 Service Manual, Brother XL6562 No Longer Available Brother Model XL6562 Sewing Machine Instruction Manual, 101 Pages Aug 8, 2011 Aug 8, 2011 Maquina de coser brother xl 3030 brazo libre en tijuana, vista previa. Guide the thread up the left channel. Brother xl 6562 6452 xr46 instruction manual.The brother website has free operation manuals. On the home XL6562 read user manual online or download in PDF format. "IMPORTANTES INSTRUCCIONES DE SEGURIDAD" Cuando se usa una maquina de coser, Creators are allowed to post content they produce to the platform, so long as they comply with our policies. United Kingdom. Company number 10637289. I once in error bought the 4505 one I think and still have it lying. But I am new at sewing so I will need a manual. Do you know where I can find one. Try this link on your computer. I just downloaded the entire manual for my Brother XL 5340.

http I dont need expert I can Have you tried contacting a Brother sewing machine dealer to. Hello i have just been given the beautiful Brother xl 5700 for my birthday my first sewing machine. and it may sound silly but I am struggling to figure out how It shows the wiring diagram for the unit. How do I get one Brother sewing machine XL 2220 Google. I found the manual for the XL 3520 through the Brother support site. Answer questions, earn points and help others. Super high amount of views. 10 sold, 992 available. More Super high amount of views. 10 sold, 992 available. You are the light of the world. For all sergers using systems 10 Pack of Serger Needles BL X 4, JL X 2 14 For all sergers using systems 10 Pack of Serger Needles BL X 4, JL X 2 11 For all sergers using system BLX1 and J LX1. Always unplug this machine from the electrical outlet immediately after using and before cleaning. 2. Always unplug before changing the light bulb. Replace bulb with same type rated 15 watts. Desconectar la maquina de la red electrica inmediatamente despues de su uso y antes de limpiarla. 2. Page 5 FOR USERS IN UK, EIRE, MALTA AND CYPRUS ONLY. If this machine is fitted with a 3 pin nonrewireable BS plug then please read the following. If the plug fitted is not suitable for the power point in your home or the cable is too short to reach a power point, then obtain an appropriate safety approved extension lead or consult your dealer. Turn on or off the switch for the main power and sewlight. Page 7 PLEASE READ BEFORE USING THIS MACHINE For safe operation 1. Be sure to keep your eye on the needle while sewing. Ne touchez pas la poulie, le levier de remontee du fil, l'aiguille, ou autre pieces mobiles. 2. Page 9 LEA ESTE MANUAL ANTES DE USAR ESTA MAQUINA Para un funcionamiento seguro 1. Este siempre atento a la aguja cuando cosa. ELEMENTOS PRINCIPALES 1 DISPOSITIVO DE BOBINADO DE LA CANILLA Pagina 26 Hace bobina para la canilla que va a ser utilizada como hilo inferior.

Fire or electric shock may result. Do not touch the plug with wet hands. Electric shock may result. When unplugging the machine, always turn off the main power first. Page 18 FONCTIONNEMENT DE LA MACHINE A COUDRE FUNCIONAMIENTO DE LA MAQUINA DE COSER Raccordement Conexion de los enchufes 1. Raccorder la fiche du cordon d'alimentation a la machine. 2. Brancher la fiche d'alimentation a une prise secteur. 1. Conecte la clavija del cordon de alimentacion a la maquina. 2. Conecte el enchufe de alimentacion a una toma de corriente. Page 20 When the foot controller is depressed lightly, the machine will run at a low speed. When the pressure on the foot controller is increased, the machine's speed will increase. Care should be taken that nothing is placed on the foot controller when the machine is not in use. CAUTION Do not allow fabric pieces and dust to collect in the foot controller. Doing so could cause a fire or an electric shock. Page 21 The sewing needle must always be straight and sharp for smooth sewing. 1 Parallel space 2 Level surface bobbin cover, glass, etc. 1 KNOWING YOUR SEWING MACHINE To Check the Needle Correctly To check the needle, place the flat side of the needle on a flat surface. Check the needle from the top and the sides. Throw away any bent needles. Page 22 Verification de l'aiguille Verificacion de la aguja L'aiguille doit toujours etre droite et pointue pour piquer correctement. La aguja de costura siempre debe estar bien recta y afilada para una buena costura. Pour controler correctement une aiguille Pour controler l'aiguille, placez le cote plat de l'aiguille sur une surface plane. Verifiez l'aiguille a partir du haut et des cotes. Jetez toutes les aiguilles tordues. If the power is on and controller is stepped on, the machine will start and may cause injury. Always use the correct presser foot for the selected stitch pattern. If the wrong presser foot is used, the needle may strike the presser foot and bend or break, and may cause injury.

Only use presser feet for this machine. Using other presser feet may lead to accident or injury. Page 24 The accessories are stored in a compartment under the flat bed attachment cover, which can be opened by flipping it toward you. TABLE OF CONTENTS Flat Bed Attachment KNOWING YOUR SEWING MACHINE STRAIGHT AND ZIGZAG STITCHING BUILTIN STITCHES Plataforma Les accessoires sont ranges dans un compartiment sous la plateau. Vous pouvez l'ouvrir en la faisant pivoter vers vous. Los accesorios estan almacenados en un compartimiento situado debajo de la tapa de la platafoma. Page 25 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 TABLE OF CONTENTS 1 XL6562 KNOWING YOUR SEWING MACHINE 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 STRAIGHT AND ZIGZAG STITCHING VARIOUS CONTROLS 3 To select a stitch, simply turn the Pattern Selection Dial, located on the right side of the machine. The Pattern Selection Dial may be turned in either direction. The following page shows the recommended range of stitch lengths and widths. Page 26 1 2 3 4 5 6 7 8 9 10 11 12 13 14 XL6452 XR46 XR52 XR65 15 16 17 18 19 20 21 22 23 24 25 26 27 DESCRIPTIF DES DIFFERENTES COMMANDES DISTINTOS MANDOS Selecteur de modele de point Selector de puntadas ATTENTION Lorsque le selecteur de modele de point est utilise pour selectionner un point, tourner le volant vers l'avant sens antihoraire a la main pour mettre l'aiguille dans sa position haute avant de selectionner le point. If the stitches get bunched together, lengthen the stitch length and continue sewing. Page 34 Selecteur de longueur de point Selector de largo de puntada En fonction du point selectionne, il est possible de regler la longueur de point pour obtenir les meilleurs resultats. Les chiffres inscrits sur le selecteur de longueur de point representent la longueur du point en millimetres mm. Il sert a coudre les boutons. Page 35 Depending on the stitch selected, you may need to adjust the stitch width.

The numbers marked on the dial represent the stitch width. THE HIGHER THE NUMBER, THE WIDER THE STITCH. 1 TABLE OF CONTENTS Stitch Width Dial 1 Stitch width dial 5 6 4 1 1 0 STRAIGHT AND ZIGZAG STITCHING NOTE When you choose the Straight Stitch or the Triple Stretch Stitch you can change the needle position from left to right. Page 36 Reverse sewing is used for back tacking and reinforcing seams. To sew in reverse, push the Reverse Sewing Lever in as far as possible and hold in that position while pressing lightly on the foot pedal. To sew forward, release the Reverse Sewing Lever. The machine will then sew forward. TABLE OF CONTENTS Reverse

Sewing Lever KNOWING YOUR SEWING MACHINE 1 Reverse sewing lever STRAIGHT AND ZIGZAG STITCHING 1 BUILTIN STITCHES Utiliser la couture en marche arriere pour arreter ou renforcer une couture. Page 37 Freearm sewing is convenient for sewing tubular and hardto reach areas on a garment. To change your machine to the freearm style, simply lift out the flat bed attachment. TABLE OF CONTENTS Converting to Freearm Style 1 Slide the flat bed attachment to the left. STRAIGHT AND ZIGZAG STITCHING 1 KNOWING YOUR SEWING MACHINE 1 Flat bed attachment 1 BUILTIN STITCHES La couture a bras libre s'impose pour des coutures tubulaires ou pour des endroits difficiles a atteindre sur des vetements. Use the spool cap large, medium, or small that is closest in size to the thread spool. If a spool cap smaller than the thread spool is used, the thread may become caught in the slit on the end of the spool. Place the bobbin onto the bobbin winder shaft and slide the bobbin winder shaft to the right. Turn the bobbin clockwise, by hand, until the spring on the shaft slides into the groove of the bobbin. KNOWING YOUR SEWING MACHINE STRAIGHT AND ZIGZAG STITCHING 6. Page 40 2. Faire passer l'extremite du fil dans le trou sur la bobine de l'interieur. Placer la bobine sur le devidoir et pousser le devidoir vers la droite.

Tourner la bobine dans le sens horaire a la main jusqu'a ce que le ressort de l'axe rentre dans la fente de la bobine. 1 Ressort de la broche 2 Rainure de la canette 3 Siege du devidoir 3. Tout en tenant l'extremite du fil, appuyer legerement sur la pedale pour bobiner le fil plusieurs fois autour de la bobine. Arrêter ensuite la machine. Page 41 CAUTION Setting the bobbin improperly may cause the thread tension to loosen, breaking the needle and resulting in injury. 1 Wound evenly 2 Wound poorly 2 CAUTION Be sure to turn off the power. MAINTENANCE 2 4. Replace the bobbin cover. Page 42 Enfilage inferieur ATTENTION Si vous n'installez pas correctement la canette, il se peut que la tension du fil se relache, que l'aiguille casse et que vous vous blessiez. 1 Bobine correctement 2 Mal bobine ATTENTION Ne pas oublier d'arreter la machine. Si la pedale est pressee accidentellement et la machine se met en marche, il est possible de se blesser. 1. Page 43 4 2 KNOWING YOUR SEWING MACHINE 5 TABLE OF CONTENTS 1 3 1. Raise the presser foot using the Presser Foot Lever. 2. Raise the needle to its highest position by turning the balance wheel toward you counterclockwise. 3. Place a spool of thread on the horizontal spool pin and press a spool cap onto the spool pin to hold the thread spool firmly in place. The thread end should come from the bottom front of the spool. Needle holder Needle threader lever Guide Hook holder 5. Page 46 Utilisation de l'enfileur Uso del enhebrador Mettre l'interrupteur principal sur "O". 1. Abaisser le levier du pieddebiche. 2. Tourner le volant vers soi sens antihoraire pour mettre le porteaiguille dans sa plus haute position. Desenchufar la maquina, interruptor principale a "O". 1. Baje la palanca de la pata del prensatelas. 2. Gire la ruedecilla hacia usted hacia la izquierda para levantar el portaagujas a tope. Page 47 1.